

Portable Water Ozonator

PWO/LC - Series

System Specification :

Model No.	:	PWO/LC - 10 / 50 / 200
Make	:	Chemtronics [®]
Feed Gas	:	Not Required
Raw Material	:	Clear Filtered Tap Water
Ozone Production	:	Instantaneous
MOC of Ozone Cell	:	Stainless Steel– 316 Grade
Cell Cooling	:	Water
Heat Dissipation	:	Not Required
Technology	:	Electrolysis
Operating Temperature	:	5°C - 40°C
Mounting / Installation	:	Submersed In Water
Line Voltage	:	110 - 240 V ac; 50/60 Hz; I Phase



PWO / LC-10

PWO / LC-200

Features :

- Feed Gas Not Required
- Dissolved Ozone From Tap Water
- High Dissolved Ozone Levels
- Works on Electrolysis principle
- Continuous mode
- Plug & Play | Instant ozone production
- Flexible Mains cord
- Portable | Light weight | Compact in size
- Water Proof Stainless Steel Body

Applications :

- Drinking Water Purification
- Water Disinfection
- Hand Sanitizer
- Equipment Disinfection
- Kill bacteria & Viruses from water
- Hospital & Medical Applications
- Sanitize surgical equipment's
- Eliminate pesticides from fruits & vegetables
- Disinfect all types of fruits and vegetables.
- Remove odour from water
- Used for Cleaning face, teeth, hair, feet and bath
- Kills bacteria's from fish, meat, chicken and other products
- Watering plants, fish tanks
- Bathing pets
- Surface cleaning and disinfection Steel Body

Accessories :

Standard ▶

- Adaptor with Switch
- Cord – 1.5 meter

Optional ▶

- Portable ORP Meter
- 12V DC Car Jack

Technical Specification:

Model No.	Ozone Water	Ozone Concentration	Size		Power	Weight
	Ltrs.	in ppm@25°C	Dia (cm)	Ht. (cm)	Watts	Gram
PWO/LC - 10	0.5 - 10	0.5 - 2.0	80	30	36	400
PWO/LC - 50	10 - 50	0.5 - 2.0	80	150	100	1,200
PWO/LC - 200	50 - 200	0.5 - 2.0	100	300	350	2,700